

# Product Data Sheet

## Description

**Nexus Marine Piston Lubricant** is blended with highly refined base oils and selected additives. Formulated with cleaning additives to promote piston cleanliness as well as control of fuel contaminants. Significantly prevents sludge and carbon formation. It is also developed to provide a high degree of water tolerance and have good water separation.

## Applications

**Nexus Marine Piston Lubricant** is recommended for medium-speed trunk piston diesel engines burning residual or marine diesel fuels. The lubricant should be used in accordance with OEM guidelines and recommendations.

## Benefits

- Ensures smooth operation by helping to provide minimum maintenance and downtime, long engine life and economical operating costs
- Helps to ensure clean crankcases, piston interiors and lubricating oil lines.
- Effective water and contaminants handling

# Product Data Sheet

	MPL30	MPL40
SAE VISCOSITY GRADE	30	40
Base Number, Mg KOH/G, ASTM D2896	30	40
Density at 15°C, kg/l, ASTM D4052	0.93	0.9
Flash Point, ASTM D 92, COC, °C/°F	190/374	200/392
Pour Point, ASTM D 97, °C/°F	-12/10	-12/10
Kinematic Viscosity @ 40°C/104°F, ASTM D 445	94	135
FZG Test, A/8.3/90, Failure Load Stage, CEC-L-07-95	12	12

\*Subject to usual manufacturing tolerances

**Nexus Marine Piston Lubricant**

20 Mar 2024

Nexus, the Nexus logo, and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.