

## Product Data Sheet

### Description

**Nexus Technosys 5W-40** is designed for use in turbocharged or naturally aspirated gasoline engines. It can also be used on diesel engines requiring API CF specifications. Suitable for standard leaded or unleaded gasoline, LPG or autogas fuel.

All driving conditions: city, road, highway.

Standards     API SN  
                    With CF performance

### Applications

Drain Interval                    : according to manufacturer's recommendations and tuned to your own use. Can be mixed with any other synthetic or mineral lubricants.

### Benefits

100% synthetic lubricant formulated with an innovative additive package to provide an outstanding anti-wear properties for better engine wear protection. Nexus's special additives provide enhanced stability to oxidation which prevents oil thickening and sludge formation problems.

# Product Data Sheet

	NEXUS TECHNOSYS 5W-40
Viscosity Grade, SAE J 300	5W-40
Kinematic Viscosity @ 40°C/104°F, ASTM D 445	40
Kinematic Viscosity @ 100°C/212°F, ASTM D 445	14.6
Viscosity Index, ASTM D2270/ISO 2909	>120
Pour Point, ASTM D97, °C/°F	-9/15.8
Flash Point – open cup method, ASTM D92/ISO 2592, °C/°F	226 / 439
Total Base Number (TBN), ASTM D2896, mgKOH/g	8.14

\*Subject to usual manufacturing tolerances

**Nexus Technosys 5W-40**

20 Mar 2024

Nexus, the Nexus logo, and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.