

Description

Nexus Textile Knitting Oil is formulated with high quality base oil, special additives and emulsifier to guarantee complete washable properties, protection against wear, rust and corrosion. The compounded emulsifier system effectively removes the oil stain from fabric by emulsifying with water and thus makes the oil completely washable

Application

Suitable for all types of knitting machine, right from full fashion machines that use nylon yarn to circular knit machines that work with tight (less dense) oils, all the high speed textile production machinery involves the use of needles, lifters, and sinkers. Available in two viscosity grades for different lubrication requirement. It can be used widely for circular or tricot machine operations by spray, bath, or mist application

BENEFITS:

- Excellent washing ability
- Special *Extreme Pressure* (EP) agent provides optimal anti-wear protection
- Maximizing knitting machine performance

	TKO22	TKO46
ISO Viscosity Grade, ASTM D 2442	22	46
Kinematic Viscosity @ 40°C/104°F, ASTM D 445	22	46
Kinematic Viscosity @ 100°C/212°F, ASTM D 445	4.05	6.12
Viscosity Index, ASTM D 2270	>100	>100
Flash Point, ASTM D 92, COC, °C/°F	>200/392	>200/392
Pour Point, ASTM D 97, °C/°F	-9/15.8	-9/15.8

*Subject to usual manufacturing tolerances

Nexus Textile Knitting Oil

20 Mar 2024

Nexus, the Nexus logo and related marks are trademarks of Nexus Limited, used under license.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Nexus or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.